



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁶:

H04B 7/185

A1

(11) International Publication Number:

WO 98/43371

(43) International Publication Date:

1 October 1998 (01.10.98)

(21) International Application Number: PCT/US98/05268

(22) International Filing Date: 18 March 1998 (18.03.98)

(30) Priority Data:

08/823,027

21 March 1997 (21.03.97)

US

(71) Applicant: ERICSSON, INC. [US/US]; 7001 Development Drive, P.O. Box 13969, Research Triangle Park, NC 27709 (US).

(72) Inventor: KARABINIS, Peter, D.; 101 Chalon Drive, Cary, NC 27511 (US).


(74) Agents: HATFIELD, Scott, C. et al.; Myers, Bigel, Sibley & Sajovec, L.L.P., P.O. Box 37428, Raleigh, NC 27627 (US).

(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

*With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*

(54) Title: SATELLITE TELECOMMUNICATIONS REPEATERS AND RETRANSMISSION METHODS



(57) Abstract

Satellite telecommunications repeaters are provided which receive, amplify, and locally retransmit the downlink signal received from a satellite thereby increasing the effective downlink margin in the vicinity of the satellite telecommunications repeaters and allowing an increase of the penetration of uplink and downlink signals into buildings, foliage, transportation vehicles, and other objects which can reduce link margin. Both portable and non-portable repeaters are provided.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

SATELLITE TELECOMMUNICATIONS REPEATERS
AND RETRANSMISSION METHODS

Field of the Invention

The present invention relates to satellite
telecommunications systems and methods, and in particular,
5 to systems and methods which can improve the link margins
between satellites and radiotelephones.

Background of the Invention

Satellite radiotelephone communications systems are
10 used widely to provide dependable, high quality
communications. See, for example, U.S. Patent No.
5,303,286 to Robert A. Wiedeman, entitled Wireless
Telephone/Satellite Roaming System.

Figure 1 is a conceptual diagram of a satellite
15 radiotelephone system. As shown in Figure 1, a satellite
radiotelephone system typically includes one or more
satellites 110, which may serve as relays or transponders
between at least one central earth station 130 and
radiotelephones 120. The earth station may in turn be
20 connected to a public switched telephone network 140,
allowing communications between satellite radiotelephones,
and communications between satellite radiotelephones and
conventional terrestrial cellular radiotelephones or
landline telephones. The satellite radiotelephone system
25 may utilize a single antenna beam covering the entire area
served by the system, or, as shown in Figure 1, the
satellite may be designed such that it produces multiple
beams 150, each serving distinct geographical coverage
areas 160 in the system's service region. Thus, a
30 cellular architecture similar to that used in conventional
terrestrial cellular radiotelephone systems can be
implemented in a satellite-based system. The satellite
110 typically communicates with a radiotelephone 120 over
a bidirectional communications pathway, with

radiotelephone communications signals being communicated from the satellite 110 to the radiotelephone 120 over a downlink (or forward link) 170, and from the radiotelephone 120 to the satellite 110 over an uplink (or reverse link) 180.

Satellite radiotelephone systems are increasingly being developed for areas where the small number of thinly scattered users and/or the rugged topography may make conventional landline telephone or cellular telephone infrastructure technically or economically impractical. Unfortunately, many of the natural features which may make it commercially impractical to install conventional landline or cellular telephone infrastructures may also impede signals traveling between radiotelephones and satellites. Dense foliage, hills, mountain ranges, and adverse weather conditions may all impede the relatively weak signals transmitted by satellites and radiotelephones.

Satellite radiotelephone systems may also serve urban areas where large buildings and other man-made structures may contribute to the degradation of satellite telecommunications signals caused by any naturally occurring features. It is also expected that a radiotelephone user will desire to use the radiotelephone while in a building or while riding in an automobile or other vehicle. The structure, mechanical operation and electrical circuitry present in an automobile or any other vehicle, and the structure of a building, along with any electrical or mechanical systems found therein or nearby, may further weaken signals traveling between satellites and radiotelephones.

The relatively small link margins involved in the typical satellite telecommunications system may be further decreased by a host of other physical processes. Both the forward and return link signals may be subject to numerous degrading conditions. For example, communications links between transmitters and receivers in mobile communications systems may be affected by channel fading.

Link degradation is generally caused by a combination of effects including multipath fading, Doppler shift due to the movement of the receiver relative to the transmitter, and additive noise.

5 Multipath fading is the result of a multipath channel existing whenever there is more than one path for the transmitted energy to travel between transmitter and receiver. For example, a satellite communications
10 downlink may have a direct path between the satellite and the mobile user plus a reflected path from the ground or from other structures. In general, the reflected path will arrive at the receiver out-of-phase with the direct path and the amplitude of the received signal will be
15 attenuated by the multipath effect. As the mobile user travels, the phase difference will generally change, resulting in a time-varying amplitude at the receiver. Multipath channel fading as predicted by the Rician channel model (when the line-of-sight path is strong compared to the reflected paths), is expected to consume
20 from 3 to 5 decibels of the available link margin. Additionally, just the proximity of a human body to the radiotelephone may also degrade the link margin by from 2 to 4 decibels.

25 In order to provide robust, stable communications, a satellite telecommunications system should generally provide signals of adequate strength to penetrate both natural and man-made obstacles which are in the signal path between the satellite and the radiotelephone. Unfortunately, satellites such as those comprising the
30 Mobile Satellite System (MSS) now being implemented in the United States by the American Mobile Satellite Corporation, are generally severely power limited so it may be difficult to offer forward link margins that compare favorably to those offered by terrestrial cellular
35 and/or Personal Communication Service (PCS) base stations. Likewise, the radiated power levels of radiotelephones are also generally limited due to the size limitations of hand-held radiotelephones and power consumption

limitations (as a function of battery charge life). Unfortunately, typical satellite antennas planned for deployment by MSS satellites are also generally size limited and thus may not be able to compensate for the low transmission power of the uplink signal transmitted by the radiotelephone. The result is both forward and reverse link margins which may be relatively small.

The MSS satellites presently planned for deployment in the 1998-2000 time frame are only expected to provide link margins on the order of 8-16 dB above the ideal additive white gaussian noise (AWGN) channel. Such link margins may necessitate an almost completely unobstructed line-of-site (LOS) path between the radiotelephone and the satellite with little link margin left over to compensate for shadowing and or blockage caused by terrain, trees, foliage, and buildings.

Summary of the Invention

In light of the foregoing, it is an object of the present invention to provide satellite telecommunications systems, components, and methods which can increase the penetration of uplink and downlink signals into buildings, foliage, transportation vehicles, and other objects which can reduce link margin.

This and other objects are accomplished according to the present invention by providing satellite telecommunications repeaters that receive, amplify, and locally retransmit the downlink signal received from a satellite thereby increasing the effective downlink margin in the vicinity of the satellite telecommunications repeaters. Furthermore, satellite telecommunications repeaters according to the present invention receive uplink signals transmitted by radiotelephones in the vicinity of the repeaters, amplify, and retransmit such signals thereby increasing the effective uplink margin.

According to one aspect of the present invention, constant gain, non-processing satellite telecommunications repeaters serve both the forward and the return links to

enable operation of hand-held radiotelephones within vehicles, buildings, airports, and in areas with heavy foliage or mountainous terrain which might not otherwise have sufficient link margin to support such communications. Patch antenna assemblies may be employed to receive and retransmit forward link signals and to receive and retransmit reverse link signals.

Non-portable, mounted satellite telecommunications repeaters may be used wherein the antennas which receive downlink signals and retransmit uplink signals are placed at a distance from and/or on the opposite side of some physical structure (such as a wall or ceiling) from the antennas which receive uplink signals and which retransmit downlink signals. These non-portable, mounted repeaters may be either mobile, such as when mounted to a vehicle, or non-mobile, such as when mounted to a building. This configuration of the non-portable, mounted repeaters of the present invention can provide greater antenna isolation, thus allowing greater repeater gain without instability. The greater gain can ultimately result in greater increase in link margins than might be had if the antennas were closer or were not separated by a barrier which tends to weaken interfering leakage signals from the retransmitting antennas of the repeaters.

Satellite telecommunications repeaters according to the invention may also be contained in single, portable, hand-held housings. These portable repeaters may have many features including a flap, or cover, into which a patch antenna assembly may be incorporated for receiving downlink signals and retransmitting uplink signals. The flap patch antenna assembly is preferably attached to the housing of the portable unit using a hinge or swivel which allows positioning of the flap/patch antenna assembly in relation to satellites to achieve a further increase in link margin. The portable repeaters may also include various types of extensions used to support the repeater housing in an operating position. According to one embodiment of the present invention, the satellite

telecommunications repeaters may employ one or more legs rotatably attached to the hand-held housing to support the repeater in an operating position.

5 According to another aspect of the present invention, the antennas of the satellite telecommunications repeaters used for receiving downlink signals from satellites and for retransmitting uplink signals to satellites may be aligned to satellites using conventional methods such as mechanical tracking and beam steering to thereby further
10 increase link margin.

According to another aspect of the present invention, the antennas of portable embodiments of the satellite telecommunications repeaters of the present invention may be physically aligned to transmitting satellites by users
15 by providing a circuit which determines the strength of signals traveling between the satellites and the repeater. By moving the repeater housing as a unit, or by only moving the antennas, until the signal strength increases, better alignment and potentially increased link margin may
20 occur.

According to another aspect of the present invention, a sleep circuit is provided for the satellite telecommunications repeaters which can place the repeater in sleep, or stand-by, mode whenever no uplink signals
25 from radiotelephones are present. This may serve to reduce satellite receiver noise and, particularly important in hand-held embodiments relying on internal battery power, to reduce power consumption by the
30 repeater.

According to another aspect of the present invention, a device is provided to hold the satellite telecommunications repeater in close proximity to a window thereby improving the ability of the repeater to increase link margins within buildings. According to a preferred
35 embodiment of the window holder device, suction cups, or some suitable alternative, hold one surface of the device in place against the surface of a window. The second surface of the device can then be rotated to a horizontal

position and be held in that position by a support rod or bar. The repeater may then be placed on the horizontal surface.

With the aid of the present invention, lighter and smaller antennas having lower gain can be used on hand-held radiotelephones and still maintain adequate link margin for satellite telecommunications. Additionally, as a result of having greater effective link margins, the radiotelephone equivalent isotropic radiated power (EIRP) level can on the average be reduced by an adaptive power control algorithm, as well as the satellite per-circuit EIRP. Less satellite per-circuit EIRP can provide higher system capacity assuming a satellite is power limited, as opposed to spectrally limited, while less phone EIRP can increase battery life for the hand-held unit.

Brief Description of the Drawings

Figure 1 illustrates a conceptual satellite communications system according to the prior art.

Figure 2 illustrates a satellite communications system incorporating repeaters of the present invention.

Figure 3 illustrates a block diagram of the repeaters of the present invention.

Figure 4 illustrates a block diagram of a signal amplifier for the apparatus of Figure 3.

Figures 5A and 5B illustrate embodiments of non-portable, mounted repeaters according to the present invention.

Figure 6 illustrates an embodiment of a portable hand-held repeater according to the present invention.

Figure 7 illustrates a device which can attach to a window to hold a portable repeater such as illustrated in Figure 6.

Detailed Description of Illustrated Embodiments

The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which embodiments of the invention are shown.

This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the invention to those skilled in the art. In the drawings, like numbers refer to like elements throughout.

Figure 2 illustrates a system including repeaters according to the present invention. As shown in Figure 2, a repeater 200 is added to the satellite telecommunications system to allow an increase in the ability of uplink signals 180 and downlink signals 170 to compensate for shadowing and or blockage caused by terrain, trees, foliage, and buildings thus effectively increasing the link margin between satellites 110 and hand-held radiotelephones 120. Before describing the satellite telecommunications repeaters of the present invention in detail, a description of the overall communications system will first be made so as to convey a complete understanding of the present invention.

Referring again to Figure 2, a downlink signal 170 from one or more satellites 110 is received by a first antenna assembly 210 which is part of the satellite telecommunications repeaters 200 of the present invention. Upon receiving the downlink signal 170, the satellite telecommunications repeater 200 amplifies the downlink signal 170 and retransmits the signal to at least one radiotelephone 120. It is understood that amplified and retransmitted downlink signals 175 may be received by any number of radiotelephones 120 within the effective signal radius of the satellite telecommunications repeaters 200. The satellite telecommunications repeaters 200 also receive uplink signals 180 transmitted by one or more radiotelephones 120. The satellite telecommunications repeaters 200 then amplify and retransmit the uplink signals to at least one orbiting satellite 110 which receives and processes the signal.

The satellite telecommunications repeaters 200 according to the present invention may be non-portable and mounted in a stand alone fixed structure or they may be attached to a building or some other structure. See
5 Figure 5A for example. Non-portable, mounted satellite telecommunications repeaters 200 may also be mounted in a transportation vehicle and thus be mobile. See Figure 5B for example. Finally, the satellite telecommunications repeaters 200 may be completely portable allowing someone,
10 such as a satellite radiotelephone user, to carry the repeater and place it so as to increase the link margin in a particular area. Figure 6 is an example of such a portable device.

The satellite telecommunications repeaters 200 of the
15 present invention do not perform signal processing. The satellite telecommunications repeaters 200 serve only to amplify and retransmit uplink and downlink signals received, thus functioning as non-processing repeaters to increase link margin and coverage. As a result, the
20 repeaters 200 may be stand-alone units and are not required to be tied to satellite switching networks or to other elements of satellite cellular or conventional cellular telephone networks.

Figure 3 is a block diagram which illustrates the
25 repeaters of the present invention in greater detail. Referring now to Figure 3, in a preferred embodiment of repeaters according to the present invention, the first antenna assembly 210 comprises a patch antenna assembly although other antennas, such as quadrifilar helix
30 antennas, may also be used. These antennas are known in the art and need not be described further herein. The first antenna assembly is further divided into a downlink receiving antenna 230 and an uplink retransmitting antenna 360.

35 A downlink signal 170 is received from one or more satellites 110 (illustrated in Figure 2) via the downlink receiving antenna 230. The downlink signal 170 is then passed through a filter 240 to eliminate noise and out of

band signals. The filtered downlink signal is then amplified using, preferably, a low noise amplifier 250. The amplified signal is applied to a second filter 260 to further eliminate any noise or out of band signals introduced by the low noise amplifier 250.

The downlink signal is then optimally passed through a signal divider 270 which produces up to N output signals 173. These output signals are then amplified by high gain, power amplifiers 280 before being retransmitted by a downlink signal retransmitting antenna 290. In the preferred embodiment of repeaters according to the present invention and as illustrated by Figure 3, the downlink retransmitting antenna 290 is part of the second antenna assembly 220 which comprises a patch antenna assembly although other antennas, such as quadrifilar helix antennas, may also be used. These antennas are known in the art and need not be described further herein. The amplified and retransmitted signals 175 are then received and processed by one or more radiotelephones 120.

The satellite telecommunications repeaters 200 also receive uplink signals 180 from one or more radiotelephones 120 (illustrated in Figure 2) by way of at least one uplink signal receiving antenna 300. In a preferred embodiment, as shown in Figure 3, the uplink receiving antenna 300 is embodied in a separate antenna that is part of the second antenna assembly 220. After the uplink signal is received by the uplink receiving antenna 300, the signal is passed through a filter 310 to eliminate noise and out of band signals. The filtered uplink signal is then amplified, preferably using a low noise amplifier 320. The amplified signal is applied to a second filter 330 to eliminate any noise or out of band signals introduced by the low noise amplifier 320. At this point, the signal is passed through a signal combiner 340 which receives up to N signals and combines them to create a single signal combiner output signal 183. The signal combiner output signal 183 is then amplified by a

power amplifier 350 and retransmitted by means of an uplink retransmitting antenna 360.

As already described, the satellite telecommunications repeaters 200 of the present invention do not perform signal processing. The satellite telecommunications repeaters 200 serve only to amplify and retransmit uplink and downlink signals received, thus functioning as non-processing repeaters to increase link margin and coverage. As a result, the repeaters 200 may be stand-alone units and are not required to be tied to satellite switching networks or to other elements of satellite cellular or conventional cellular telephone networks. Although the repeaters may include additional circuitry which detects or monitors the uplink signals 180 and/or the downlink signals 170 and performs some function as a result of a characteristic of those signals, there is no processing of the actual uplink signals 180 and the downlink signals 170 themselves.

In the present invention, the overall gain produced by amplification of the downlink signal 170 or the uplink signal 180 is preferably maintained at or below the isolation between antenna combinations 230, 290 and 300, 360, respectively. Referring to Figure 4, if the overall gain is greater than the isolation between a corresponding antenna pair (for example, 300, 360), oscillation will occur. Overall Gain is defined as the relationship of the strength of the input signal (P_i) to the output signal (P_o) expressed according to the following formula:

$$\text{Overall Gain} = 10 \log (P_o/P_i) \text{ in dB.}$$

The overall gain produced by the satellite telecommunications repeaters of either the uplink or the downlink signal should not exceed the corresponding antenna pair isolation because the system may become unstable. Isolation is defined as the relationship of the received signal (P_r) in response to a transmitted signal (P_t) expressed according to the following formula:

$$\text{Isolation} = 10 \log (P_r/P_t) \text{ in dB.}$$

For a satellite telecommunications repeater sufficiently small to be embodied in a hand-held unit, it is expected that a gain of 15 dB is acceptable. The maximum allowable gain, however, will greatly depend on many factors including but not limited to the exact design specifications of the embodiment of the satellite telecommunications repeater, particularly the types of receiving and transmitting antennas employed and the relative location of the antennas. In any case, the satellite telecommunications repeater system is preferably limited to the case where:

$$[\text{Isolation}]_{\text{dB}} + [\text{Gain}]_{\text{dB}} < 0$$

in order to prevent the occurrence of instability.

Specific embodiments of the non-portable, mounted satellite telecommunications repeaters of the present invention are illustrated in Figures 5A and 5B. The non-portable, mounted embodiments of the satellite telecommunications repeaters of the present invention may allow operation of hand-held radiotelephones in structures where the link margins might not be otherwise sufficient to support communications.

Referring to Figure 5A, for example, satellite telecommunications repeaters can be mounted on buildings 550 to allow satellite telecommunications signals to penetrate such structures. The first antenna assembly 210 may be mounted on a window or on the roof a building 550 and that the second antenna assembly 220 may be physically separate and placed on the inside of the building. As illustrated in Figure 5A, the second antenna assembly 220 could be placed on a wall or ceiling of an interior office.

Non-portable, mounted embodiments of the satellite telecommunications repeaters of the present invention could also be mounted in mobile transportation vehicles, such as automobiles, buses, trains, ships, or airplanes. As seen in Figure 5B, for example, the first antenna assembly 210 could be mounted on the top of the roof, trunk, or hood of an automobile, or might even be

incorporated into an existing antenna assembly 590. The second antenna assembly 220 could then be placed at a convenient location in the passenger area of the automobile.

5 It is preferred that non-portable, mounted satellite telecommunications repeaters have a physical structure between the first and second antenna assemblies 210, 220. Given that non-portable, mounted repeaters according to the present invention may possibly be less restricted as
10 to size, it is anticipated that any prior art means of aligning the repeaters to satellites may be used including, mechanical tracking and beam steering.

In these non-portable embodiments it is preferred to separate the first antenna assembly 210 from the second
15 antenna assembly 220. Generally, the greater the physical separation of these assemblies, the greater the antenna isolation which in turn permits greater gain to be produced by the satellite telecommunications repeaters without causing instability of the system. It is thus
20 also advantageous to separate the two antenna assemblies by using a physical structure, such as a wall or ceiling or a large ground plane.

Figure 6 illustrates a preferred embodiment of the present invention in which a satellite telecommunications
25 repeater is embodied in a completely portable hand-held unit. Portable hand-held satellite telecommunications repeaters include a housing 610 with multiple surfaces on which may be placed the antennas for receiving uplink signals 300, the antenna for retransmitting downlink
30 signals 290, the antenna for receiving downlink signals 230, and the antenna for retransmitting uplink signals 360. The housing 610 is preferably made of a conductive frame which serves both to contain and protect the electronics of the satellite telecommunications repeaters
35 and also serves as an antenna ground plane.

In addition, a flap or cover 620 may be attached to the housing 610. The flap 620 may be attached to the repeater housing 610 by any suitable method that allows

the flap 620 to rotate or pivot from a closed position and to move in relation to the repeater housing 610. For example, one or more hinges may be use to attach the flap 620 to the radiotelephone. One or more of the antennas of the repeater of the present invention may then be placed on the flap 620 which would increase the antenna isolation.

In a preferred embodiment of the present invention, the antenna for receiving uplink signals 300, and the antenna for retransmitting downlink signals 290 are placed on a first face 615 of the repeater housing 610. The antenna for receiving downlink signals 230 and the antenna for retransmitting uplink signals 360 are preferably placed on the flap 620, but may be placed on another face of the housing as long as the proper relationship between repeater gain and antenna isolation are maintained. Placing the antenna for receiving downlink signals 230 and the antenna for retransmitting uplink signals 360 on the flap or cover 620 also may allow for aligning the antennas 230, 360 with satellites 110 to further increase link margin.

Many other features may also be disposed on the housing 610 or flap 620 of hand-held satellite telecommunications repeaters according to the present invention. For example, an ON/OFF indicator 640 may be disposed on a face of a housing to give ready indication of the power status of the satellite telecommunications repeaters. A switch 650 may be located on a face of the housing for turning the repeater 200 on or off. The preferred embodiment of the hand-held satellite telecommunications repeaters will also include a battery power source preferably contained within the housing 610. Additionally, it may also be desired to provide connections on a face of the repeater housing 610 allowing for a plug-in 660 source of power from an AC wall outlet or from a DC power source such as an automobile cigarette lighter socket.

Also as shown in Figure 6, the preferred hand-held embodiment of the present invention may be supported in an upright position by one or more leg members 670. It is understood that a single leg may be used as illustrated in Figure 6, or that a second leg may be added on the side opposite the first leg. Preferably, two leg members 670, one on each side of the satellite telecommunications repeater housing 610, are rotatably attached to the housing 610. The present invention also contemplates one or more support members pivotally attached to the back face of the unit to similarly support the unit in an upright position. These different means of support are intended to support satellite telecommunications repeaters in a position to allow alignment with a satellite. Thus, the term upright as used herein does not mean completely vertical, but is rather an expansive term meaning the range of positions which are not substantially horizontal.

As with non-portable, mounted embodiments of the present invention, the design of antennas which are suitable for portable embodiments of satellite repeaters of the present invention are well known to those of ordinary skill in this art and need not be described in detail herein. It is, however, preferred to use a patch antenna system for the portable hand-held embodiment of Figure 6.

Due to the size, power requirements and battery capacity associated with a portable, hand-held repeater of the present invention, it is preferred that such a unit be equipped with a circuit that places its transmitter in stand-by mode when uplink signals from a radiotelephone are not present. One of ordinary skill in the art would be able to provide a circuit of this type or of any comparable type to provide a stand-by operation.

The portable hand-held embodiment of the present invention may be aligned to satellites by moving the downlink receiving antenna 230 portion of the hand-held unit to achieve the best reception and transmission between satellites and radiotelephones 120. It is also

understood that a conventional signal strength meter or other indicator can be provided which will sample the strength of a downlink signal and give a read-out of the strength. If this is employed, the user of the hand-held
5 satellite telecommunications repeater may change the position the downlink receiving antenna 230 until an increased or a maximum signal strength is received.

Portable satellite telecommunications repeaters of the present invention can potentially be more effective
10 when placed in close proximity to windows in buildings rather than positioned further in the interior of the building or positioned next to walls. Devices for mounting portable hand-held satellite telecommunications repeaters of the present invention are thus provided.

15 **Figure 7** illustrates such a device for mounting a satellite telecommunications repeater on a window.

As seen in **Figure 7**, the window mounting device comprises a first surface member 710 and a second surface member 720 which are rotatably connected at an edge of the
20 first surface member 710 and the second surface member 720. Although any type of rotatable connection between the two surface members is acceptable, a rotating hinge 850 is the preferred method of joining the two surface members. The first surface member 710 is equipped with
25 some means for mounting the device 700 on a window surface 750. Although the first surface member 710 may be permanently attached to the window 750, for example with some type of adhesive, it is more preferred that the device 700 be releaseably mounted to the window 750 thus
30 keeping the device 700 portable and capable of being used in different locations with a portable, hand-held satellite telecommunications repeater. One such preferred method of releaseably attaching the device 700 to a window surface 750 is provided by attaching the first surface
35 member 710 to a window 750 with one or more suction cups 760 which may themselves be permanently or releaseably attached to the first surface member 710. The second surface member 720 can be rotated into a position

essentially perpendicular to the first surface member 710 to allow placement of satellite telecommunications repeaters 200 on the second surface member 720. The second surface member 720 may be maintained in a horizontal orientation by a support bar 730.

In one embodiment, a first end 740 of the support bar 730 is attached to the second surface member 720 at a point. The attachment may be made by any connection that allows arcuate movement of the support bar 730 at the attachment point 740. A second end 790 of the support bar 730 is slidably attached to the first surface member 710 such that the support bar 730 slides between a first, closed position and a second, opened position. At the point the second end 790 reaches the opened position, a detent, snap, or other means is provided to keep the second end 790 in the opened position. It is understood that the attachments of the support member to the first surface member 710 and the second surface member 720 may be reversed without detrimental effect. Additionally, it is expected that a support member 730 may be slidably mounted to both the first surface member 710 and the second surface member 720 and that detents, snaps, or other means may be provided on both the first surface member 710 and the second surface member 720 to maintain the device an opened position.

In the drawings and specification, there have been disclosed typical embodiments of the invention and, although specific terms are employed, they are used in a generic and descriptive sense only and not for purposes of limitation, the scope of the invention being set forth in the following claims.

THAT WHICH IS CLAIMED:

1. A satellite telecommunications repeater comprising:

means for receiving downlink satellite telecommunication signals from at least one satellite;

5 means for amplifying said downlink satellite telecommunication signals, said means for amplifying said downlink satellite telecommunication signals having a first gain;

10 means for retransmitting said downlink satellite telecommunication signals from said at least one satellite to at least one radiotelephone, said means for retransmitting said downlink satellite telecommunication signals having a first isolation from said means for receiving said downlink satellite telecommunication
15 signals;

means for receiving uplink satellite telecommunication signals from said at least one radiotelephone;

20 means for amplifying said uplink satellite telecommunication signals from said at least one radiotelephone, said means for amplifying said uplink satellite telecommunication signals having a second gain; and

25 means for retransmitting said uplink satellite telecommunication signals from said at least one radiotelephone to said at least one satellite, said means for retransmitting said uplink telecommunication signals having a second isolation from said means for receiving said uplink satellite telecommunication signals;

30 wherein said first gain produced by said means for amplifying said downlink satellite telecommunication signals does not exceed said first isolation, and wherein said second gain produced by said means for amplifying said uplink satellite telecommunication signals does not
35 exceed said second isolation.

2. The satellite telecommunications repeater of Claim 1:

wherein said uplink and said downlink satellite telecommunications signals are only amplified and are not processed by said satellite telecommunications repeater.

3. The satellite telecommunications repeater of Claim 1:

wherein said means for receiving said downlink satellite telecommunication signals from said at least one satellite is disposed in a first antenna;

wherein said means for receiving said uplink satellite telecommunication signals from said at least one radiotelephone is disposed in a second antenna.

4. The satellite telecommunications repeater of Claim 3:

wherein both said first antenna is a patch antenna and said second antenna is a patch antenna.

5. The satellite telecommunications repeater of Claim 1:

further comprising a portable hand-held housing; wherein said satellite telecommunications repeater is embodied in said portable hand-held housing.

6. The satellite telecommunications repeater of Claim 5:

wherein said means for receiving said downlink satellite telecommunications signals and said means for retransmitting said uplink satellite telecommunications signals further comprises a patch antenna assembly integral with a flap movably mounted to said satellite telecommunications repeater.

7. The satellite telecommunications repeater of Claim 5:

5 further comprising at least one extension on said mobile unit;

wherein said portable hand held housing is maintained at a desired orientation by said at least one extension from said portable hand held housing single
10 mobile unit which may be positioned to place said housing in said desired orientation.

8. The satellite telecommunications repeater of Claim 7:

5 wherein said at least one extension from said single mobile unit comprises at least one leg member rotatably attached to said portable hand held housing.

9. The satellite telecommunications repeater of Claim 5 in combination with a device for placing said satellite telecommunications repeater in close proximity to a window comprising:

5 a first surface;
a second surface;

means for releasably attaching said first surface to a window in a parallel orientation;

10 wherein said first surface is rotatably connected to said second surface so as to allow said second surface to rotate from a position parallel to said first surface to a position perpendicular to said first surface to thereby allow the satellite telecommunications repeater to be mounted thereon; and

15 means for maintaining said second surface in a position perpendicular to said first surface.

10. The satellite telecommunications repeater of Claim 1 further comprising:

5 means, responsive to said means for receiving said downlink telecommunications signals, for aligning said satellite telecommunications repeater in relation to

said at least one satellite to increase received signal strength.

11. The satellite telecommunications repeater of Claim 10 further comprising:

means, responsive to said means for receiving said downlink telecommunications signals, for determining said downlink signal strength; and

an operator display of downlink signal strength such that the satellite telecommunications repeater can be aligned in relation to said at least one satellite to achieve increased received signal strength.

12. The satellite telecommunications repeater according to Claim 1 further comprising:

means for sensing absence of said uplink satellite telecommunication signals from said at least one radiotelephone; and

means, responsive to said sensing means, for placing said satellite telecommunications repeater in standby mode.

13. A satellite radiotelephone communications system comprising:

at least one satellite;

at least one radiotelephone;

means for processing satellite radiotelephone telecommunication signals between said satellite and said radiotelephone; and

a satellite telecommunications repeater placed in sufficient proximity to said radiotelephone to receive, amplify, and retransmit uplink and downlink satellite telecommunication signals between said satellite and said radiotelephone; said satellite telecommunications repeater further comprising:

means for receiving downlink satellite telecommunication signals from at least one satellite;

means for amplifying said downlink satellite telecommunication signals from said at least one satellite;

20 means for retransmitting said downlink satellite telecommunication signals from said at least one satellite to at least one radiotelephone;

means for receiving uplink satellite telecommunication signals from said at least one radiotelephone;

25 means for amplifying said uplink satellite telecommunication signals from said at least one radiotelephone; and

30 means for retransmitting said uplink satellite telecommunication signals from said at least one radiotelephone to at least one satellite.

14. The satellite radiotelephone communications system of Claim 13:

5 wherein the gain produced by said means for amplifying said downlink signal is less than the isolation required for stability of said means for receiving and amplifying said downlink signal, and further wherein the gain provided by said means for amplifying said uplink signal is less than the isolation required for stability of said means of receiving and amplifying said uplink
10 signal.

15. The satellite radiotelephone communications system of Claim 14:

further comprising a portable hand-held housing;
5 wherein said satellite telecommunications repeater is embodied in said portable hand-held housing.

16. The satellite radiotelephone communications system of Claim 15:

5 wherein said means for receiving said downlink satellite telecommunications signals and said means for retransmitting said uplink satellite telecommunications

signals further comprises a patch antenna assembly integral with a flap movably mounted to said housing of said satellite telecommunications repeater.

17. The satellite radiotelephone communications system of Claim 15:

5 further comprising at least one extension on said housing;

10 wherein said portable hand-held housing is maintained at a desired orientation by said at least one extension from said portable hand held housing single mobile unit which may be positioned to place said housing in said desired orientation.

18. The satellite radiotelephone communications system of Claim 15 comprising:

5 a device for placing said satellite telecommunications repeater in close proximity to a window, said device comprising:

a first surface;

a second surface;

10 means for releasably attaching said first surface to a window in a parallel orientation;

15 wherein said first surface is rotatably connected to said second surface so as to allow said second surface to rotate from a position parallel to said first surface to a position perpendicular to said first surface to thereby allow the satellite telecommunications repeater to be mounted thereon; and

means for maintaining said second surface in a position perpendicular to said first surface.

19. The satellite radiotelephone communications system of Claim 15 further comprising:

5 means, responsive to said means for receiving said downlink telecommunications signals, for aligning said satellite telecommunications repeater in relation to

said at least one satellite to increase received signal strength.

20. The satellite radiotelephone communications system of Claim 15 further comprising:

means, responsive to said means for receiving said downlink telecommunications signals, for determining said downlink signal strength; and

an operator display of downlink signal strength such that the satellite telecommunications repeater can be aligned in relation to said at least one satellite to achieve increased received signal strength.

21. The satellite radiotelephone communications system of Claim 15 further comprising:

means for sensing absence of said uplink satellite telecommunication signals from said at least one radiotelephone;

means responsive to said sensing means for placing said satellite telecommunications repeater in standby mode.

22. A method of satellite radiotelephone communications comprising the steps of:

receiving downlink satellite telecommunication signals from at least one satellite;

amplifying said downlink satellite telecommunication signals;

retransmitting said downlink satellite telecommunication signals to at least one radiotelephone;

receiving uplink satellite telecommunication signals from said at least one radiotelephone;

amplifying said uplink satellite telecommunication signals; and

retransmitting said uplink satellite telecommunication signals to said at least one satellite.

23. The method of satellite radiotelephone communications according to Claim 22 wherein the gain of said amplifying steps does not exceed the isolation between corresponding receive-transmit antenna pairs.

24. The method of satellite radiotelephone communications according to Claim 22 wherein said steps of receiving, amplifying and retransmitting are performed within a portable hand-held housing.

25. The satellite radiotelephone communications method of Claim 22 further comprising the steps of:

sensing said uplink satellite telecommunication signals from said at least one radiotelephone; and

5 placing said satellite telecommunications repeater in standby mode, in response to sensing absence of said uplink satellite telecommunications signals.

10 26. A satellite telecommunications repeater comprising:

means for receiving downlink satellite telecommunication signals from at least one satellite;

means for amplifying said downlink satellite telecommunication signals;

15 means for retransmitting said downlink satellite telecommunication signals from said at least one satellite to at least one radiotelephone;

means for receiving uplink satellite telecommunication signals from said at least one
20 radiotelephone;

means for amplifying said uplink satellite telecommunication signals from said at least one radiotelephone; and

25 means for retransmitting said uplink satellite telecommunication signals from said at least one radiotelephone to said at least one satellite.

27. The satellite telecommunications repeater of Claim 26:

5 wherein said uplink and said downlink satellite telecommunications signals are only amplified and are not processed by said satellite telecommunications repeater.

28. The satellite telecommunications repeater of Claim 26:

further comprising a portable hand-held housing; wherein said satellite telecommunications repeater is embodied in said portable hand-held housing.

29. The satellite telecommunications repeater of Claim 26 further comprising:

5 means, responsive to said means for receiving said downlink telecommunications signals, for aligning said satellite telecommunications repeater in relation to said at least one satellite to increase received signal strength.

30. The satellite telecommunications repeater of Claim 29 further comprising:

5 means, responsive to said means for receiving said downlink telecommunications signals, for determining said downlink signal strength; and

an operator display of downlink signal strength such that the satellite telecommunications repeater can be aligned in relation to said at least one satellite to achieve increased received signal strength.

31. The satellite telecommunications repeater according to Claim 26 further comprising:

5 means for sensing absence of said uplink satellite telecommunication signals from said at least one radiotelephone; and

means, responsive to said sensing means, for placing said satellite telecommunications repeater in standby mode.

FIG. 1
PRIOR ART




FIG. 2




FIG. 3




FIG. 4




FIG. 5B




FIG. 5A




FIG. 6





FIG. 7



6/6

INTERNATIONAL SEARCH REPORT

In ☐ National Application No

PCT/US 98/05268

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04B7/185

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 724 336 A (NIPPON ELECTRIC CO) 31	13,22,26
Y	July 1996 see abstract see column 2, line 5-32 see column 3, line 6-11 see column 4, line 13-26 see column 5, line 53 - column 6, line 5 see column 7, line 26-35 see column 8, line 30-43 see figures 1,2,4 see claims 1,5,6 ---	1-3,14, 23,25, 27,29,31
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

26 August 1998

Date of mailing of the international search report

04/09/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Dejonghe, O

INTERNATIONAL SEARCH REPORT

In ational Application No
PCT/US 98/05268

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 302 455 A (ORION INDUSTRIES) 8 February 1989 see page 2, line 28-33 see page 3, line 53-58 see page 5, line 11-21 see figure 1 see claims	1-3,14, 23,27
Y A	--- EP 0 570 325 A (ISRAEL STATE) 18 November 1993 see abstract see column 1, line 1-16 see column 1, line 21-43 see column 2, line 25-41 see figure 4 see claims 1,3	29 5-8,10, 15-17, 19,24,28
Y A	--- US 5 134 708 A (MARUI KUNIYOSHI ET AL) 28 July 1992 see abstract see column 1, line 35-51 see column 2, line 32-45 see column 3, line 51-54 see column 4, line 16-34 see column 6, line 29-38 see figures 4,6 -----	25,31 11,12, 20,21

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/05268

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0724336	A	31-07-1996	JP 8265250 A	11-10-1996
			NO 960329 A	29-07-1996
EP 0302455	A	08-02-1989	US 4941200 A	10-07-1990
			DE 3885369 D	09-12-1993
			DE 3885369 T	24-03-1994
			ES 2047510 T	01-03-1994
			FI 883617 A,B,	04-02-1989
			JP 1051730 A	28-02-1989
			US 5023930 A	11-06-1991
			US 5115514 A	19-05-1992
			US 5093923 A	03-03-1992
			US 5065449 A	12-11-1991
			US 5152002 A	29-09-1992
			US 5168574 A	01-12-1992
EP 0570325	A	18-11-1993	IL 101875 A	31-12-1995
			JP 7135412 A	23-05-1995
US 5134708	A	28-07-1992	JP 1086724 A	31-03-1989
			CA 1307829 A	22-09-1992
			DE 3889832 D	07-07-1994
			DE 3889832 T	08-09-1994
			EP 0310379 A	05-04-1989
			US 4996715 A	26-02-1991

THIS PAGE BLANK (USPTO)